

LT15


LIFTING TABLE 150 kg



The scissor lift table with foot-operated hydraulic pump is the ideal tool for a variety of lifting and loading operations and for use as “work station” to provide improved ergonomic conditions together with improved productivity. It represents the best solution for the manual load handling, combining functioning, cost saving, safety and health of operator during work.

COMPACTNESS

- The table is equipped with a folding handlebar that, when fully closed, becomes very compact and can be stored in a convenient, space saving way.
- Sturdy steel machine designed to transport and pick your goods becoming your reliable partner in the everyday work.
- Easy handling granted by ergonomic handle and the combination of fixed and steering polyurethane wheels.



EASY OF USE

- Thanks to the efficient hydraulic foot pump the table can be brought to the desired height to easily pick or raise working materials.
- With the lever on the handle it is possible to lower the table without clicks with the utmost precision.



SAFETY

- The foot brakes on the steering wheels guarantee perfect stability during operations.
- The practical wheel guards on the steering wheels protect the feet while working.
- The objects raised at an individual and ergonomic height greatly reduce the strain on your back.
- The appropriate inspection supports fix the platform in case of maintenance or cleaning work.



APPLICATION FIELDS

Lift tables are perfect for order preparation and goods mobilization. They are commonly used throughout industry and commerce, including factories, warehouses, retail outlets, printers, schools, colleges, laboratories, banks and offices.



Description

Load capacity	Kg	150
Material		Steel
Scissor type		Single scissor
Push handle type		Folding
Weight	Kg	40
Handle height	mm	880
Pumping time no load	n.	19
Nombre de coups de pompe avec charge	n.	23

Lift

Min. height	mm	210
Max. height	mm	720
Lifting distance	mm	510
Lift function		Foot pedal

Table size

Height	mm	35
Width	mm	450
Depth	mm	700

Wheels

Wheels material		Polyurethane
Wheels locking function		Yes
Fixed wheels	n.	2
Swivel wheels	n.	2
Diameter of the wheels	mm	100

The information is aligned with the Data file at the time of download. Printed on 10/06/2021 (ID 10310)

©2021 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

